



RELIABILITY BUILT IN™



EUROPEAN BASIC CATALOG

— *featuring* —

T&S iLine *and* UtilityLine



RELIABILITY BUILT IN™

Backed by the quality and reliability of T&S, our iLine and UtilityLine features stylish solutions at a cost-effective price point.

Pre-Rinse Units	2
Pre-Rinse Units	2-3
Low Profile Pre-Rinse Units	4
Faucets	5-8
Accessories	9-10



THE utilityline



EX-1DP00-H



EX-1DP12-H

Model Number	Inlet Type (D)	Mounting Hole	Clearance	Nozzle (Length)	Spray Valve Flow Rate	AOF Flow Rate	Stocking Article
EX-1DP00-H	Compression Fittings for 15mm OD Copper Tubing	48mm	N/A	N/A	15L/min	N/A	No
EX-1DP12-H	Compression Fittings for 15mm OD Copper Tubing	48mm	97mm	305mm	15L/min	15L/min	Yes

Single hole, deck-mount pre-rinse unit with single lever temperature control, 18" flexible supply hose, check valves, and compression fittings for 15mm OD copper tubing. Optional 305mm (12") add-on faucet.

Zweiloch-Geschirrbräuse mit Einhebelmischer zur Wandmontage mit schwenkbarem Auslauf mit 305mm Länge (Ø18mm). Keramikartusche, Messing, glanzverchromt. Handbräuse 21,2 l/min Durchlauf.

THE
utilityline



EX-6WP12-H

Model Number	Inlet Type (D)	Mounting Hole	Nozzle (Length)	Spray Valve Flow Rate	AOF Flow Rate	Stocking Article
EX-6WP12-H	G 1/2" Male	2 x 25mm, ca.150mm	305mm	15L/min	15L/min	Yes

Double-hole, wall-mount pre-rinse unit with single lever temperature control and 150mm center body. G 1/2" male inlets, and 305mm add-on faucet.

Zweiloch-Geschirrbrause mit Einhebelmischer zur Wandmontage mit schwenkbarem Auslauf mit 305mm Länge (Ø18mm). Keramikartusche, Messing, glanzverchromt. Handbrause 21,2 l/min Durchlauf.

THE utilityline



EX-1DMP06-H



EX-1DMP08-H

Model Number	Inlet Type (D)	Mounting Hole	Clearance	Nozzle (Length)	Spray Valve Flow Rate	AOF Flow Rate	Stocking Article
EX-1DMP06-H	Compression Fittings for 15mm OD Copper Tubing	38mm	97mm	152mm	15L/min	15L/min	Yes
EX-1DMP08-H	Compression Fittings for 15mm OD Copper Tubing	38mm	97mm	203mm	15L/min	15L/min	Yes

Single hole, deck-mount low-profile pre-rinse units with single lever temperature control, flexible supply hoses, check valves, and compression fittings for 15mm OD copper tubing. 152mm (6") or 203mm(8") add-on faucet option.

Einloch-Geschirrbrause mit Einhebelmischer zur Aufschmottung in niedriger Ausführung, wahlweise mit schwenkbarem

iLine
by 



EA-1DF08-300



EA-1DF08-500

Model Number	Inlet Type (D)	Mounting Hole	Clearance	Nozzle (Length)	AOF Flow Rate	Stocking Article
EA-1DF08-300	G 1/2" Female	38mm	218mm	204mm	15L/min	Yes
EA-1DF08-500	G 1/2" Female	38mm	371mm	204mm	15L/min	Yes

Single-hole, deck-mount faucets with single levers and G 1/2" female inlets, and stainless steel supply hoses.

Einloch-Armatur mit Einhebelmischer zur Auftischmontage, mit schwenkbarem Auslauf mit 200mm Länge (Ø25mm). 60mm Montageschaft, G1/2" AG. Keramikartusche, Messing, glanzverchromt.



EA-1DF09-LH



EA-1DF09

Model Number	Inlet Type (D)	Mounting Hole	Clearance	Nozzle (Length)	AOF Flow Rate	Stocking Article
EA-1DF09-LH	G 1/2" Female	38mm	122mm	230mm	15L/min	No
EA-1DF09	G 1/2" Female	38mm	122mm	230mm	15L/min	Yes

Single-hole, deck-mount faucets with single levers and G 1/2" female inlets, and stainless steel supply hoses.

Einloch-Armatur mit Einhebelmischer, wahlweise mit langem Griff, zur Aufschmottung, mit schwenkbarem Auslauf mit 230mm Länge. 60mm Montageschaft, G1/2" AG. Keramikartusche, Messing, glanzverchromt.



EA-6WF08



EA-6WF10

Model Number	Inlet Type (D)	Mounting Hole	Nozzle (Length)	Flow Rate
EA-6WF08	G 1/2" Male	25mm	202mm	15L/min
EA-6WF10	G 1/2" Male	25mm	254mm	15L/min

Double-hole, wall-mount faucet with single lever temperature control and 150mm center body. G 1/2" male inlets and 152mm (6") or 203mm(8") add-on faucet lengths.

Zweiloch-Armatur mit Einhebelmischer, wahlweise mit langem Griff, zur Wandmontage, mit schwenkbarem Auslauf mit 200mm Länge. Keramikartusche, Messing, glanzverchromt.



EA-2DF09



EA-2DF12-150



EA-2DF12-300

Model Number	Inlet Type (D)	Mounting Hole	Clearance	Nozzle (Length)	Flow Rate	Stocking Article
EA-2DF09	G 1/2" Female	38mm	190mm	229mm	21L/min	Yes
EA-2DF12-150	G 1/2" Female	38mm	150mm	300mm	21L/min	No
EA-2DF12-300	G 1/2" Female	38mm	300mm	300mm	21L/min	No

Single-hole, deck-mount faucets with single levers and G 1/2" female inlets, and stainless steel supply hoses.

Einloch-Zweigriff-Mischarmatur zur Auftischmontage, mit schwenkbarem Auslauf in verschiedenen Längen. Armatur wahlweise um 150mm oder 300mm erhöht. 60mm Montageschaft, G1/2" AG. 90° Keramikkartuschen, Messing, glanzverchromt

THE utilityline

Wok Range Faucets



- EX-1WWF08
- EX-1WWF10
- EX-1WWF12
- EX-1WWF14

Wok/range faucet with 20 cm (8”), 25 cm (10”), 30 cm (12”) and 36 cm (14”) swing nozzle, full flow

Pre-Rinse Accessories



EX-ADF00
Add-on faucet, no nozzle



EX-ADF12
Add-on faucet with 30 cm (12”) swing nozzle, full flow

Single Temperature Faucets



EX-1WSF-A
Single hole single temperature wall-mount sill faucet

Aerator



EX-0199-23
Self-closing water saver aerator with 7.6 cm (3”) stainless steel activation rod

Foot Pedal Valve



EX-SFPV
Single foot pedal valve

THE utilityline

Rinsers



EX-RINSER-1

Can/jar rinser unit, small
18 x 17 cm (7" x 7.6") pan



EX-RINSER-SV06

Spray head replacement
for EX-RINSER-3



EX-RINSER-SV06B

Spray stem replacement
for EX-RINSER-3



EX-RINSER-2

Can/jar rinser unit, medium
33 x 18 cm (13" x 7") pan



EX-RINSER-SV06S

Star bracket replacement
for all EX-RINSERS



EX-RINSER-3

Can/jar rinser unit, large
63 x 22 cm (24.75" x
8.625") pan



EX-RINSER-SV13

Spray head replacement
for EX-RINSER-1 and
EX-RINSER-2



RELIABILITY BUILT IN™

tsbrass.com
internationalsales@tsbrass.com
+1 864 834 4102