

# SAFE-T-LINK GAS CONNECTORS



**WELDED FITTINGS:**  
Will not pull off under stress

**FREESPIN FITTING:**  
360-degree rotation prevents twisting of hose during appliance movement

**EXTRUDED COATING:**  
Unlike dipped coatings, does not intrude on braid and maintains even thickness for strength and flexibility

**SWIVELINK SWIVEL:**  
Increased mobility and space savings



**STRESS-LITE CORRUGATED HOSE:**  
Reduced stress on inner tube boosts flexibility and durability

**YELLOW COLOR:**  
Complies with ASME A 13.1 color designation for hazardous materials

**STAINLESS STEEL BRAIDED HOSE:**  
Machine braided tight fit provides increased tensile strength vs. gapped braid

**OPTIONAL QUICK-DISCONNECTS:**  
Available for wall and appliance ends



**MULTIPLE SIZE OPTIONS:**  
24" to 72" lengths and 1/2" NPT to 1" NPT internal thread and diameters

**LEADING HOSE STRENGTH:**  
Requires 64% more force to kink hose vs. competitors

**LONG-LASTING DURABILITY:**  
Last 2.5 times as long as competitors in appliance pull-away tests

**AVAILABLE ACCESSORIES**  
support application needs and increased safety compliance

**SUPERIOR CONSTRUCTION**  
for safety and performance

**SAFE-T-GUARD™**  
safety shut-off valve prevents gas flow when disconnected

**5-YEAR WARRANTY**

**POSI-SET™**  
wheel placement system available