

Pre-Rinse Accessories

TAG:

5AFL12


Add-On Faucet

Architect/Engineering Specifications:

Add-on faucet with polished chrome plated brass body, 3/8" NPT female outlet, 12" swing nozzle with laminar full flow device, equip ceramic cartridge, lever handle and 3/8" NPT male inlet. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372. Meets ADA ANSI/ICC A117.1 requirements.

Job Name	
Model Specified	Quantity
Variations Specified	
Date	







Features & Benefits:

- · Add-on faucet w/ polished chrome plated brass body
- 3/8" NPT female outlet
- 12" equip swing nozzle w/ laminar full flow device
- Quarter-turn ceramic cartridge
- · equip lever handle
- 3" nipple w/ 3/8" NPT male inlet
- Material: Polished chrome plated brass body, tubular spout, nipple and chrome plated metal handle

Product Compliance:





- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)

Warranty: One Year (Limited)

LOW LEAD COMPLIANT

ADA Compliant

Performance Data:



Temperature: 40 °F - 140 °F [4.44 °C - 60 °C]

• Flow Rate: 4.52 GPM [17.11 L/min] @ 60 psi [4.14 bar]







