

Medical and Lavatory Faucets

TAG:


B-2320-CR-WS


Centerset Lavatory Faucet

Architect/Engineering Specifications:

4" centerset deck mount mixing faucet with polished chrome plated brass body, swivel/rigid gooseneck, 1.5 GPM aerator, ceramic cartridges with check valves, lever handles and 1/2" NPSM male inlets. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372. Meets ADA ANSI/ICC A117.1 requirements.

Job Name				
Model Specified	Quantity			
Variations Specified				
Date				







- 4" centerset deck mount mixing faucet w/ polished chrome plated brass body
- 2 15/16" swivel gooseneck
- Lock washer included for rigid applications
- 1.5 GPM aerator, Series 1 (B-0199-01-WS)
- Quarter-turn Cerama cartridges with check valves to prevent crossflow of water
- · Lever handles with color coded indexes
- 1/2" NPSM male inlets with coupling nuts
- Material: Polished chrome plated brass cast body & tubular spout and chrome plated metal handles

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)

Warranty: One Year (Limited)

® Us



Performance Data:

Pressure: 20 - 125 psi [1.38 - 8.62 bar]

Temperature: 40°F - 140°F [4.44°C - 60°C]

Flow Rate: 1.5 GPM [5.68 L/min] @ 60 psi [4.14 bar]

Optional Handles



Optional Outlets (Series 1 / VR Series 6)

GPM	Aerated	Non-Aerated (Laminar)	VR Aerated	VR Non-Aerated (VR Laminar)	□ 4" Wrist Action □ Lever (Standard)
0.35	N/A	□ B-0199-01-N035	N/A	□ B-0199-06-N035	□ 4-Arm
0.5	N/A	□ B-0199-01-N05	N/A	□ B-0199-06-N05	
1.0	□ B-0199-01-F10) N/A	□ B-0199-06-F10	N/A	Ontional Cartridges With Checks
1.2	□ B-0199-01-F12	2 □ B-0199-01-LF12	□ B-0199-06-F12	□ B-0199-06-LF12	Optional Cartridges With Checks
1.5	Standard	□ B-0199-29	□ B-0199-06-WS	□ B-0199-29VR	□ Quarter-Turn Cerama w/ Check Valve (Standard)
22	□ B-0199-01	□ B-0199-21	□ B-0199-06	□ B-0199-21-VRF	□ Quarter-Turn Fterna w/ Spring Check







