| TAG: | |
|------|--|


Sill Faucet

Architect/Engineering Specifications:

Single hole, single temperature, wall mount faucet with polished chrome plated brass body, garden hose male outlet, compression cartridge with spring check, key or screwdriver controlled handle and 1/2" NPT female inlet. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372.

| Job Name | |
|----------------------|----------|
| Model Specified | Quantity |
| Variations Specified | |
| Date | |







Features & Benefits:

- · Single hole, single temperature wall mount faucet
- · Garden hose male outlet
- · Eterna compression cartridge w/ spring check
- Key or screwdriver controlled handle
- 1/2" NPT female inlet with \emptyset 2" flange
- Material: Polished chrome plated brass body

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)



Warranty: One Year (Limited)

Performance Data:

- Pressure: 20 125 psi [1.38 8.62 bar]
- Temperature: 40 °F 140 °F [4.44 °C 60 °C]
- Flow Rate: 9.10 GPM [34.45 L/min] @ 60 psi [4.14 bar]

Optional Handles

Optional Cartridges

- ☐ 4" Wrist Action
- □ Lever
- □ 4-Arm

- □ Quarter- Turn Cerama w/ Check Valve
- □ Quarter-Turn Eterna w/ Spring Check









