

SABER Certified T&S Products

Faucets and Pre-Rinse Units are required to comply with the technical regulation for water efficiency tools under the SASO standards 2655 and 2656.

T&S Brass and Bronze Works Inc. received the corresponding certifications for the following list of products:



Part Number	Product Description	Spray Valve	Flow Rate	Add-On Faucet / Flow Rate	Wall Bracket
PRE-RINSE UNITS					
 B-0113-B	<i>EasyInstall Single Hole Base, 46 cm (18") Flex Lines</i>	B-0107	4.35 L/min (1.15 GPM)	–	✓
 B-0113-12V15-B	<i>EasyInstall Single Hole Base, 46 cm (18") Flex Lines</i>	B-0107		30 cm (12") 5.7 L/min (1.5 GPM)	✓
 B-0123-12V15-B	<i>EasyInstall Double Hole Deck Mount, 20 cm (8") Centers, 46 cm (18") Flex Lines</i>	B-0107		30 cm (12") 5.7 L/min (1.5 GPM)	✓
 B-0123-12V15-BC	<i>EasyInstall Double Hole Deck Mount, 20 cm (8") Centers, 46 cm (18") Flex Lines</i>	B-0107-C	2.46 L/min (0.65 l/min)	30 cm (12") 5.7 L/min (1.5 GPM)	✓
 B-0133-12V15-B	<i>EasyInstall Wall Mount 20 cm (8"), 46 cm (18") Flex Lines</i>	B-0107	4.35 L/min (1.15 GPM)	30 cm (12") 5.7 L/min (1.5 GPM)	✓
 B-0133-B	<i>EasyInstall Wall Mount 20 cm (8"), 46 cm (18") Flex Lines</i>	B-0107		–	✓
 B-0114-01B-WH4	<i>EasyInstall Single Hole Base, 46 cm (18") Flex Lines with Retractable Swivel Arm</i>	B-0107		–	✓
5PR-2S00	<i>Equip Single Hole Pre-Rinse, 46 cm (18") Flex Lines</i>	5SV	4.35 L/min (1.15 GPM)	–	✓
5PR-2S12V15	<i>Equip Single Hole Pre-Rinse, 46 cm (18") Flex Lines</i>	5SV		30 cm (12") 5.7 L/min (1.5 GPM)	✓
Part Number	Product Description	Spout	Outlet / Flow Rate		
LOW FLOW ELECTRONIC SENSOR FAUCETS					
 EC-3142-VF05	<i>Low Flow ChekPoint Above-Deck Electronic Faucet</i>	Contemporary Spout	Vandal-Resistant Spray Device	1.89 L/min (0.5 GPM)	
Part Number	Product Description	Swing Nozzle / Swivel Gooseneck	Outlet / Flow Rate		
FAUCETS - PREP, PANTRY, SINK					
 B-0221-V15	<i>Deck Mount, 20 cm (8") Centers, ½" NPT Male Inlet</i>	Swing Nozzle, 30 cm (12") (062X-V15)	Vandal-Resistant Aerator	5.7 L/min (1.5 GPM)	
 B-0226-V15	<i>Deck Mount, 10 cm (4") Centers</i>	Swing Nozzle, 25 cm (10") (061X-V15)			
 B-0226-V15-WH4	<i>Deck Mount, 10 cm (4") Centers, Eterna Cartridges, 10 cm (4") Wrist Handles</i>	Swing Nozzle, 25 cm (10") (061X-V15)			
 B-0231-V15	<i>Wall Mount, 20 cm (8") Centers</i>	Swing Nozzle, 30 cm (12") (062X-V15)			
 5F-2SLX12V15	<i>Equip Deck Mount, Single Hole Base</i>	Swing Nozzle, 30 cm (12")			
 5F-8DLX12V15	<i>Equip Deck Mount, 20 cm (8") Centers</i>	Swing Nozzle, 30 cm (12")			
BAR SINK / HAND SINK FAUCETS					
 B-1141-2-V15-CR	<i>Workboard Faucet, Deck Mount, 10 cm (4") Centers, Cerama Cartridges</i>	Swivel Gooseneck, 11 cm (4¾") (179X-V15)	Vandal-Resistant Aerator	5.7 L/min (1.5 GPM)	

Please see the back page for images of our T&S SABER Certified Products

A selection of our SABER Certified T&S Products



B-0107
Spray Valve



EC-3142-VF05
Sensor Faucet

T&S's products meet the flow rates required by SABER / SASO:

- SABER / SASO required flow rate for Spray Valves and Faucets <6 L/min

💧 T&S flow rate / Pre-Rinse Units: 4.35 L/min

💧 T&S flow rate / Faucets: 5.7 L/min

- SABER / SASO required flow rate for Sensor Faucets <1.9 L/min

💧 T&S flow rate / Sensor Faucets: 1.89 L/min



B-0221-V15
Faucet



B-0226-V15-WH4
Faucet



B-0113-12V15-B



B-0226-V15-WH4



B-1141-2-V15-CR



B-0133-12V15-B



5F-8DLX12V15



EC-3142-VF05

