



Could your faucets save you more money?



THE **utilityline**

Introducing Our **NEW CEF SENSOR FAUCETS**



CEF-1DG



CEF-1DS



CEF-4DS

Hand-washing is an essential part of operating a kitchen safely. But with many hand sink faucets delivering water at 15 L/min or more, the amount of water – and money – wasted can really add up. By simply adding a T&S CEF Sensor Faucet, you can significantly reduce the amount of water wasted while still maintaining a clean and healthy kitchen.

That's what our **CEF Sensor Faucets** were designed to do – a sanitary alternative that will save you money and reliably and effectively work hard at a surprisingly modest cost.

Even minor investments have a huge impact on saving water, energy, and money! The larger the facility and the more changes you make, the higher the savings will be.

SEE THE BACK OF THIS FLYER for specific models and specifications for each series of CEF Sensor Faucets



RELIABILITY BUILT IN™

www.tsbrass.com

internationalsales@tsbrass.com

2 Saddleback Cove • P.O. Box 1088 • Travelers Rest, SC 29690 U.S.A.
Main Office +1 864-834-4102

CEF SENSOR FAUCET MODELS

Suffix	Description
VF05	With non-aerated 1.9 L/min flow rate
ST	Single-temperature

CEF-1DS Series



This series is comprised of versions of the same base model CEF-1DS. Each is a single-hole, deck-mounted sensor faucet with a cast spout, has a vandal-resistant 8.3 L/min flow rate aerator unless otherwise stated, and includes: AC/DC transformer, a control module, a mechanical mixing valve (for dual temperature only), and G ½" flexible supply hose(s).

Product	Flow Rate	Temperature	Body/Nozzle Type	Mounting
CEF-1DS	8.3 L/min aerated	Dual	Cast Spout	Deck
CEF-1DS-VF05	1.9 L/min aerated	Dual	Cast Spout	Deck
CEF-1DS-ST	8.3 L/min aerated	Single	Cast Spout	Deck
CEF-1DS-ST-VF05	1.9 L/min non-aerated	Single	Cast Spout	Deck

CEF-1DG Series



This series is comprised of versions of the same base model CEF-1DG. Each is a single-hole, deck-mounted sensor faucet with a swivel gooseneck, has a vandal-resistant 8.3 L/min flow rate aerator unless otherwise stated, and includes: AC/DC transformer, a control module, a mechanical mixing valve (for dual temperature only), and G ½" flexible supply hose(s).

Product	Flow Rate	Temperature	Body/Nozzle Type	Mounting
CEF-1DG	8.3 L/min aerated	Dual	Swivel Gooseneck	Deck
CEF-1DG-VF05	1.9 L/min non-aerated	Dual	Swivel Gooseneck	Deck
CEF-1DG-ST	8.3 L/min aerated	Single	Swivel Gooseneck	Deck

CEF-4DS Series



This series is comprised of versions of the same base model CEF-4DS. Each is a single-hole, deck-mounted sensor faucet with a cast spout, has a vandal-resistant 8.3 L/min flow rate aerator unless otherwise stated, and includes: AC/DC transformer, a control module, a mechanical mixing valve (for dual temperature only), and G ½" flexible supply hose(s).

Product	Flow Rate	Temperature	Body/Nozzle Type	Mounting
CEF-4DS	8.3 L/min aerated	Dual	Cast Spout	Deck
CEF-4DS-VF05	1.9 L/min non-aerated	Dual	Cast Spout	Deck
CEF-4DS-ST	8.3 L/min aerated	Single	Cast Spout	Deck



RELIABILITY BUILT IN™

www.tsbrass.com

internationalsales@tsbrass.com

2 Saddleback Cove • P.O. Box 1088 • Travelers Rest, SC 29690 U.S.A.
Main Office +1 864-834-4102