

the perfect **SENSOR FAUCET** *for* **4" CENTER RETROFITS**



A MORE EFFICIENT, HYGIENIC SOLUTION FOR RETROFITS

Discover the **EC-3104**, **EC-3105** and **EC-3107**
sensor faucets from T&S.

The EC-3104, EC-3105 and EC-3107 families include mounting hardware that allows operators to replace deck- or wall-mounted manual two-hole faucets with touch-less sensor faucets — all without the need to alter existing hole configurations.

- Convert manual 2-hole deck- and wall-mount applications to a more efficient hygienic touch-less sensor faucet.
- Designed to accommodate 4" center-to-center, deck- and wall-mount installations.
- Water-resistant control module with internal flow control switches.
- Customizable auto time-out and shut-off delay settings.
- Optional auto-flush feature flows water for 30 seconds after every 12 inactive hours.
- Plus much more!




Visit tsbrass.com/c/sensor-faucets today!

2 Saddleback Cove • P.O. Box 1088 • Travelers Rest, SC 29690 • Toll-Free 800-476-4103 • Phone 800-476-4103 • Fax 800-868-0084



EC-3104

4" deck mount electronic sensor faucet with polished chrome plated brass body with integral spout, 2.2 GPM vandal resistant aerator, AC/DC control module with internal flow control setting switches, temperature control mixing valve with integral check valves and 18" flexible stainless steel supply hoses with 3/8" compression connections. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9, NSF 372 and UL 1951. Meets ADA ANSI/ICC A117.1 requirements.



Model	Description	Outlet
EC-3104	4" Deck Mount c/c Two Hole, Cast Spout, AC/DC Control Module	VR 2.2 GPM Aerator
EC-3104-HG	4" Deck Mount c/c Two Hole, Cast Spout, Hydro-Generator, AC/DC Control Module	VR 2.2 GPM Aerator
EC-3104-LF22	4" Deck Mount c/c Two Hole, Cast Spout, AC/DC Control Module	VR 2.2 GPM Laminar Flow Device
EC-3104-LMV	4" Deck Mount c/c Two Hole, Cast Spout, Less Mixing Valve, AC/DC Control Module	VR 2.2 GPM Aerator
EC-3104-TMV	4" Deck Mount c/c Two Hole, Cast Spout, Thermostatic Mixing Valve, AC/DC Control Module	VR 2.2 GPM Aerator
EC-3104-VF05	4" Deck Mount c/c Two Hole, Cast Spout, AC/DC Control Module	VR 0.5 GPM Non-Aerated
EC-3104-VF05THG	4" Deck Mount c/c Two Hole, Cast Spout, Thermostatic Mixing Valve, Hydro-Generator, AC/DC Control Module	VR 0.5 GPM Non-Aerated
EC-3104-VF05-HG	4" Deck Mount c/c Two Hole, Cast Spout, Hydro-Generator, AC/DC Control Module	VR 0.5 GPM Non-Aerated
EC-3104-VF5-TMV	4" Deck Mount c/c Two Hole, Cast Spout, Thermostatic Mixing Valve, AC/DC Control Module	VR 0.5 GPM Non-Aerated
EC-3104TMVHGF10	4" Deck Mount c/c Two Hole, Cast Spout, Thermostatic Mixing Valve, Hydro-Generator, AC/DC Control Module	VR 1.0 GPM Aerator



EC-3105

4" wall mount electronic sensor faucet with polished chrome plated brass body with 4 1/8" rigid gooseneck, 2.2 GPM vandal resistant aerator, AC/DC control module with internal flow control setting switches, temperature control mixing valve with integral check valves and 18" flexible stainless steel supply hoses with 3/8" compression connections. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9, NSF 372 and UL 1951. Meets ADA ANSI/ICC A117.1 requirements.




Model	Description	Outlet
EC-3105	4" Wall Mount c/c Two Hole, Rigid Gooseneck, AC/DC Control Module	VR 2.2 GPM Aerator
EC-3105-HG	4" Wall Mount c/c Two Hole, Hydro-Generator AC/DC Control Module	VR 2.2 GPM Aerator
EC-3105-LF22	4" Wall Mount c/c Two Hole, Rigid Gooseneck, AC/DC Control Module	VR 2.2 GPM Laminar Flow Device
EC-3105-LMV	4" Wall Mount c/c Two Hole, Less Mixing Valve, AC/DC Control Module	VR 2.2 GPM Aerator
EC-3105-TMV	4" Wall Mount c/c Two Hole, Rigid Gooseneck, Thermostatic Mixing Valve, AC/DC Control Module	VR 2.2 GPM Aerator
EC-3105-VF05	4" Wall Mount c/c Two Hole, Rigid Gooseneck, AC/DC Control Module	VR 0.5 GPM Non-Aerated
EC-3105-VF12	4" Wall Mount c/c Two Hole, Rigid Gooseneck, AC/DC Control Module	VR 1.2 GPM Aerator
EC-3105-VF5-TMV	4" Wall Mount c/c Two Hole, Rigid Gooseneck, Thermostatic Mixing Valve, AC/DC Control Module	VR 0.5 GPM Non-Aerated
EC-3105TMVHGF10	4" Wall Mount c/c Two Hole, Rigid Gooseneck, Thermostatic Mixing Valve, AC/DC Control Module	VR 1.0 GPM Aerator



EC-3107

4" deck mount electronic sensor faucet with polished chrome plated brass body with 4 1/8" rigid gooseneck, 2.2 GPM vandal resistant aerator, AC/DC control module with internal flow control setting switches, temperature control mixing valve with integral check valves and 18" flexible stainless steel supply hoses with 3/8" compression connections. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9, NSF 372 and UL 1951. Meets ADA ANSI/ICC A117.1 requirements.



Model	Description	Outlet
EC-3107	4" Deck Mount c/c Two Hole, Rigid Gooseneck, AC/DC Control Module	VR 2.2 GPM Aerator
EC-3107-HG	4" Deck Mount c/c Two Hole, Rigid Gooseneck, Hydro-Generator, AC/DC Control Module	VR 2.2 GPM Aerator
EC-3107-LF22	4" Deck Mount c/c Two Hole, Rigid Gooseneck, AC/DC Control Module	VR 2.2 GPM Laminar Flow Device
EC-3107-LMV	4" Deck Mount c/c Two Hole, Rigid Gooseneck, Less Mixing Valve, AC/DC Control Module	VR 2.2 GPM Aerator
EC-3107-TMV	4" Deck Mount c/c Two Hole, Rigid Gooseneck, Thermostatic Mixing Valve, AC/DC Control Module	VR 2.2 GPM Aerator
EC-3107-VF05	4" Deck Mount c/c Two Hole, Rigid Gooseneck, AC/DC Control Module	VR 0.5 GPM Non-Aerated
EC-3107-VF05-HG	4" Deck Mount c/c Two Hole, Rigid Gooseneck, Hydro-Generator, AC/DC Control Module	VR 0.5 GPM Non-Aerated
EC-3107-VF05THG	4" Deck Mount c/c Two Hole, Rigid Gooseneck Thermostatic Mixing Valve, Hydro-Generator, AC/DC Control Module	VR 0.5 GPM Non-Aerated
EC-3107-VF5-TMV	4" Deck Mount c/c Two Hole, Rigid Gooseneck, Thermostatic Mixing Valve, AC/DC Control Module	VR 0.5 GPM Non-Aerated
EC-3107-VF12	4" Deck Mount c/c Two Hole, Rigid Gooseneck, AC/DC Control Module	VR 1.2 GPM Aerator
EC-3107-7XF1THG	4" Deck Mount c/c Two Hole, Rigid Gooseneck, Thermostatic Mixing Valve, Hydro-Generator, AC/DC Control Module	VR 1.0 GPM Aerator