

# **Electronic Faucets** 5EF-1D-DS-V5THG


## TAG:


### **Electronic Sensor Faucet**

#### **Architect/Engineering Specifications:**

Single hole deck mount electronic sensor faucet with polished chrome plated brass body and 0.5 GPM vandal resistant non-aerated spray device, Hydro-generator power supply, AC/DC control module, thermostatic temperature control mixing valve with integral check valves and 18" flexible stainless steel supply hoses with 3/8" compression connections. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9, NSF 372, UL 1951 and ASSE 1070. Meets ADA ANSI/ICC A117.1 requirements.

Job Name Model Specified Quantity Variations Specified Date









#### Features & Benefits:

- Single hole deck mount faucet w/ polished chrome plated brass body
- 0.5 GPM vandal resistant non-aerated spray device, Series 9 (B-0199-09-N05)
- Hydro-generator power supply
- Water resistant control module
- Plug in AC transformer or (4) AA battery (DC) power options
- Thermostatic temperature mixing valve w/ integral check valves
- 18" flexible stainless steel supply hoses w/ 3/8" compression connections
- Low battery LED indicator light
- Material: Polished chrome plated brass body & tubular spout

#### **Product Compliance:**




- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)
- UL 1951ASSE 1070 (TMV)
- ASSE 1070 (TMV)

Warranty: One Year (Limited)



#### Performance Data:





Flow Rate: 0.5 GPM [1.9 L/min] @ 60 psi [4.14 bar]

Water Consumption: @ 10 sec = .08 gal [ .30 L] @ 15 sec = .13 gal [ .49 L]

Optional Outlets (Series 4 / VR Series 9	)
Non-Aerated	

GPM	Aerated	Non-Aerated (Laminar)	VR Aerated	VR Non-Aerated (VR Laminar)	Optional Deck Plates
0.35	N/A	□ B-0199-04-N035	N/A	□ B-0199-09-N035	□ 4" Chrome Plated Brass Deck Plate
0.5	N/A	□ B-0199-04-N05	N/A	Standard	□ 8" Chrome Plated Brass Deck Plate
1.0	N/A	N/A	N/A	□ B-0199-09-LF10	= c cincina i latea Brase Best i late
1.5	□ B-0199-04-WS	N/A	□ B-0199-09-WS	□ B-0199-09-LF15	
2.2	□ B-0199-04	□ B-0199-25	□ B-0199-09	□ B-0199-27	









