Aluminum Spray Unit







Architect/Engineering Specifications:

Single temperature wall mount faucet with polished chrom plated brass body, compression cartridges with spring checks, 4-arm handle, vacuum breaker, add-on faucet with compression cartridge and lever handle, 6" swing nozzle with stream regulator outlet, 90 degree swivel adapter, 9 ft coiled hose with angled aluminum spray valve, hose hanger hook, and 1/2" NPT female inlet. Certified to ASME A112.18.1 / CSA B125.1 and CSA B64.8.

Job Name	
Model Specified	Quantity
Variations Specified	
Date	





Features & Benefits:

- Single temperature wall mount faucet with polished chrome plated brass body
- Quarter-turn Eterna compression cartridge w/ spring check
- 4-arm handle with blue coded index
- EasyInstall 3/8" continuous pressure vacuum breaker
- Add-on faucet w/ polished chrome plated brass body
- 6" swing nozzle w/ stream regulator outlet, Series 1
- 90° swivel adapter
- 9 ft coiled hose w/ angled aluminum spray valve
- Hose hanger hook w/ mounting screws
- 1/2" NPT female Inlet
- Materials: Polished chrome plated body & tubular spout, chrome plated metal handles, polyurethane hose and aluminum spray valve

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Exempt (Non-Potable)
- CSA B64.8 (VB)



Warranty: One Year (Limited)

Performance Data:

Pressure: 20 - 125 psi Temperature: 40 °F - 140 °F

Flow Rate:

Spray Valve: 2.54 GPM @ 60 psi Add-on Faucet: 3.18 GPM @ 60 psi

Optional Cartridges With Checks

Optional Add-On Faucet Outlets (Series 1 / VR Series 6)

,,			- p	opiionai cararageo rrian circone	
GPM	Aerated	VR Aerated	☐ 4" Wrist Action ☐ Lever	☐ Quarter-Turn Cerama w/ Check Valve☐ Quarter-Turn Eterna w/ Spring Check (Standard)	
1.0	□ B-0199-01-F10	□ B-0199-06-F10	☐ 4-Arm (Standard)	,	
1.5	□ B-0199-01-WS	□ B-0199-06-WS	,		
2.2	□ B-0199-01	□ B-0199-06			

Optional Handles







