

Epoxy Coated Retractable Hose Reel

B-7232


Open Epoxy Coated Hose Reel


TAG:

Architect/Engineering Specifications:

Open epoxy coated hose reel, 3/8" NPT male outlet, 3/8" x 35' heavy-duty non-marking hose, ratcheting system, multi-fit bracket, adjustable hose bumper, 3/8" NPT female inlet and 3/8" NPT male outlet.

Job Name	
Model Specified	Quantity
Variations Specified	
Date	







Features & Benefits:

- Open epoxy coated hose reel
- 3/8" x 35' heavy-duty non-marking hose rated to 300 PSI
- Ratcheting system holds the length of hose until a slight tug to retract automatically
- 3/8" NPT female inlet
- 3/8" NPT male outlet
- Adjustable hose bumper
- Multi-fit bracket for wall, ceiling or under counter mounting
- Optional 3/8" NPT stainless steel swivel between hose and spray gun available
- Material: Epoxy coated open reel and wall bracket

Product Compliance:

NSF 61 Exempt (Non-Potable)

Warranty: Two Year (Limited)

Hose: One Year (Limited)

Performance Data:

Air/Water Pressure: 300 psi Max

Temperature: 40 °F - 200 °F

Flow Rate: 4.20 GPM @ 60 psi

(Outlet Device &/or Final Configuration May Reduce Flow Rate)

Optional Hose Reel Spray Valves

Med Flow Spray Valve □ B-0107 □ B-0108

Ergonomic Medium Flow Spray Valve □ B-0108-H Ergonomic High Flow Spray Valve

High Flow Spray Valve □ EB-0107 □ EB-2322

Extended Spray Wand Stainless Steel Rear Trigger Water Gun □ MV-2516-24 Stainless Steel Front Trigger Water Gun Aluminum Rear Trigger Water Gun □ MV-2522-24 □ MV-3516-24

T&S BRASS AND BRONZE WORKS, INC.

Optional Hose Reel Multi-Fit Brackets 1/4", 3/8", & 1/2" Stainless Steel Hose Reel

□ G019430-45 EasyInstall Stainless Steel Wall Swing Bracket

□ G016652-45 **Deck Mount Pivot Bracket**

□ G018477-45 Stainless Steel Table Leg Swing Bracket







