


Single Lever Faucet

TAG:

Architect/Engineering Specifications:

Deck mount single lever faucet with 10" deck plate, polished chrome plated brass body with integral 9" swivel spout, polished chrome plated deck plate, 2.2 GPM aerator, ceramic cartridge with adjustable temperature limit stop, 6" single lever handle and 16" flexible stainless steel supply hoses with 3/8" O.D. compression connections. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372. Meets ADA ANSI/ICC A117.1 requirements.



Features & Benefits:

- Deck mount single lever faucet with polished chrome plated brass body w/ integral 9" swivel spout
- Polished chrome plated brass 10" deck plate cover (fits 8" hole centers)
- 2.2 GPM aerator, Series 4 (B-0199-04)
- Ceramic cartridge w/ adjustable temperature limit stop
- 6" single lever handle w/ color coded index
- 16" flexible stainless steel supply hoses with 3/8" O.D. compression connections
- Material: Polished chrome plated brass body & deck plate, chrome plated metal handle and stainless steel hoses

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)



Ceramic Cartridge: Two Year (Limited)

ADA Compliant

Performance Data:

Pressure: 20 - 125 psi [1.38 - 8.62 bar] Temperature: 40 °F - 140 °F [4.44 °C - 60 °C]

Flow Rate: 2.2 GPM [8.33 L/min] @ 60 psi [4.14 bar]



GPM	Aerated	Non-Aerated (Laminar)	VR Aerated	VR Non-Aerated (VR Laminar)	Accessories
0.35	N/A	□ B-0199-04-N035	N/A	□ B-0199-09-N035	
0.5	N/A	□ B-0199-04-N05	N/A	□ B-0199-09-N05	□ 6" Long Handle (Standard)
1.0	N/A	N/A	N/A	□ B-0199-09-LF10	
1.2	□ B-0199-04-F12	2 N/A	□ B-0199-09-F12	N/A	
1.5	□ B-0199-04-WS	S N/A	□ B-0199-09-WS	□ B-0199-09-LF15	
2.2	Standard	□ B-0199-25	□ B-0199-09	□ B-0199-27	







T&S BRASS AND BRONZE WORKS, INC.



