
# Workboard Mixing Faucet

# **Architect/Engineering Specifications:**

3 1/2" deck mount mixing faucet with chrome plated brass body, 5 3/4" swivel gooseneck with 2.2 GPM aerator, compression cartridges with spring checks, lever handles, 1/2" NPT male inlets and chrome plated escutcheon. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372. Meets ADA ANSI/ICC A117.1 requirements.



# 7 1/8" [182mm] 0 2" [51mm] 11 9/16" [294mm] 1/4" [6mm] Maximum Thickness

### Features & Benefits:

- 3 1/2" deck mount mixing faucet w/ chrome plated brass body
- 5 3/4" swivel gooseneck
- 2.2 GPM aerator, Series 1 (B-0199-01)
- Quarter-turn Eterna compression cartridges with internal spring checks to prevent cross flow of water
- · Lever handles w/ color coded indexes
- 1/2" NPT male inlets
- Tailpieces and nuts for 1/4" NPT male connections
- Chrome plated escutcheon
- Material: Chrome plated brass body & tubular spout and chrome plated metal handles & escutcheon

Non-Agrated

## **Product Compliance:**

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)

Warranty: One Year (Limited)

### LOW LEAD COMPLIANT

### Performance Data:

Pressure: 20 - 125 psiTemperature: 40 °F - 140 °F

Flow Rate: 2.2 GPM @ 60 psi



### Optional Outlets (Series 1 / VR Series 6)

GPM	Aerated	(Laminar)	VR Aerated	(VR Laminar)	Optional Handles
0.35	N/A	□ B-0199-01-N035	N/A	□ B-0199-06-N035	☐ 4" Wrist Action
0.5	N/A	□ B-0199-01-N05	N/A	□ B-0199-06-N05	□ Lever (Standard)
1.0	□ B-0199-01-F10	N/A	□ B-0199-06-F10	N/A	
1.5	□ B-0199-01-WS	□ B-0199-29	□ B-0199-06-WS	□ B-0199-29VR	Optional Cartridges
2.2	Standard	□ B-0199-21	□ B-0199-06	□ B-0199-21-VRF	<ul><li>□ Quarter-Turn Cerama w/ Check Valve</li><li>□ Quarter-Turn Eterna w/ Spring Check (Standard)</li></ul>

VP Non-Agrated







T&S BRASS AND BRONZE WORKS, INC.

