



# Replacement Hoses

## B-0020-HC



TAG:

### Hose w/ Spray Nozzle

#### Architect/Engineering Specifications:

20" flexible stainless steel hose with heat resistant handle and 0.65 GPM low flow fan jet spray head, 3/4-14 UN female inlet. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372.

Job Name \_\_\_\_\_  
 Model Specified \_\_\_\_\_ Quantity \_\_\_\_\_  
 Variations Specified \_\_\_\_\_  
 Date \_\_\_\_\_



#### Features & Benefits:

- 20" flexible stainless steel hose with heat resistant gray handle
- 0.65 GPM low flow fan jet spray head
- Polyurethane inner tubing
- 3/4-14 UN female inlet
- Hose washer included
- Material: Polished chrome plated brass end fittings, thermoplastic handle and stainless steel hose

#### Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 - Section 9
- NSF 372 (Low Lead Content)

**Warranty:** One Year (Limited)

#### Performance Data:

- Pressure: 20 - 125 psi
- Temperature: 40 °F - 140 °F
- Flow Rate: 0.65 GPM @ 60 psi



T&S BRASS AND BRONZE WORKS, INC.



• 2 Saddleback Cove • Travelers Rest, SC 29690  
 Ph 800-476-4103 • Fax 864-834-3518  
 • Simi Valley, CA • Ph 800-423-0150 • www.tsbrass.com

Date: 09/20/19