

Epoxy Coated Retractable Hose Reels

B-7212-01-PPB


Open Epoxy Coated Hose Reel

TAG:

Architect/Engineering Specifications:


Open epoxy coated steel hose reel, high flow spray valve with swivel, 3/8" x 15' heavy-duty non-marking hose, ratcheting system, multi-fit bracket, adjustable hose bumper, 3/8" NPT female inlet and 345 degree epoxy coated pivot deck mount bracket with reel-to-bracket mounting hardware.

Job Name	
Model Specified	Quantity
Variations Specified	
Date	



Features & Benefits:

- Open epoxy coated steel hose reel
- Blue high flow spray valve w/ swivel
- 3/8" x 15' heavy-duty non-marking hose rated to 300 PSI
- Ratcheting system holds the length of hose until a slight tug to retract automatically
- 3/8" NPT female inlet
- Adjustable hose bumper
- Multi-fit bracket for wall, ceiling or under counter mounting
- 345 degree epoxy coated pivot deck mount bracket designed with reel-to-bracket mounting hardware
- Material: Epoxy coated steel open reel and wall bracket, polished chrome plated spray valve, epoxy coated steel pivot bracket





Product Compliance:

- NSF 61 Exempt (Non-Potable)
- EPAct 2005 Non-Compliant (PRSV)

Warranty: Two Year (Limited) Hose: One Year (Limited)

Performance Data:

Pressure: 20 - 125 psi Temperature: 40 °F - 140 °F Flow Rate: 3.70 GPM @ 60 psi

Optional Hose Reel Spray Valves

□ B-0107 Med Flow Spray Valve Ergonomic Medium Flow Spray Valve □ B-0108 Ergonomic High Flow Spray Valve □ B-0108-H High Flow Spray Valve (Standard) Extended Spray Wand Stainless Steel Rear Trigger Water Gun □ EB-0107 □ EB-2322 □ MV-2516-24 □ MV-2522-24 Stainless Steel Front Trigger Water Gun

Optional Hose Reel Multi-Fit Brackets 3/8" x 15', 30', & 35' Epoxy Coated Hose Reel

□ G019430-45 EasyInstall Stainless Steel Swing Bracket □ G016636-45 **Epoxy Coated Wall Swing Bracket** □ G016652-45 Deck Mount Pivot Bracket (Standard) □ G018477-45 Stainless Steel Table Leg Swing Bracket



□ MV-3516-24





Aluminum Rear Trigger Water Gun

