
Wall Mount Mixing Faucet

Architect/Engineering Specifications:

8" wall mount mixing faucet with polished chrome plated brass body, 9 1/8" swing nozzle with stream regulator outlet, compression cartridges with spring checks, 4-arm handles and 1/2" NPT female inlets. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372. Meets ADA ANSI/ICC A117.1 requirements.

Job Name	
Model Specified	Quantity
Variations Specified	
Date	



9 1/8" [232mm] 6 1/4" [159mm] 3 1/4" 82mm 2 3/8" [61mm]

Features & Benefits:

- 8" wall mount mixing faucet with polished chrome plated brass body
- 9 1/8" Swing nozzle w/ stream regulator outlet
- Lock washer provided for rigid application
- Quarter-turn Eterna compression cartridges w/ spring checks to prevent cross flow of water
- 4-arm handles w/ color coded indexes
- 1/2" NPT female eccentric inlets w/ Ø2" flanges
- Adjustable centers from 7 3/4" to 8 1/4"
- Material: Polished chrome plated brass body and tubular spout and chrome plated metal handles

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)

Warranty: One Year (Limited)



Performance Data:

Pressure: 20 - 125 psi Temperature: 40 °F -140 °F

Flow Rate: 23.09 GPM @ 60 psi



Optional Outlets (Series 2 / VR Series 7)

CDM	A a water al	Non-Aerated	VD Assets d	VR Non-Aerated	Optional Handles
GPM	Aerated	(Laminar)	VR Aerated	(VR Laminar)	□ 4" Wrist Action
0.35	N/A	□ B-0199-02-N035	N/A	□ B-0199-07-N035	□ Lever
0.5	N/A	□ B-0199-02-N05	N/A	□ B-0199-07-N05	□ 4-Arm (Standard)
1.0	□ B-0199-02-F10	N/A	□ B-0199-07-F10	N/A	,
1.2	□ B-0199-02-F12	N/A	□ B-0199-07-F12	N/A	Optional Cartridges With Checks
1.5	□ B-0199-02-WS	N/A	□ B-0199-07-WS	N/A	,
2.2	□ B-0199-02	N/A	□ B-0199-07	N/A	□ Quarter-Turn Cerama w/ Check Valve
					□ Quarter-Turn Eterna w/ Spring Check (Standard)







