

Angled Spray Head Unit

Architect/Engineering Specifications:

Single hole, single temperature wall mount faucet with polished chrome plated brass body, compression cartridge with spring check, lever handle, vacuum breaker, 9 ft coiled hose with angled high flow spray head and 1/2" NPT female inlet. Certified to ASME A112.18.1/CSA B125.1 and CSA B64.8.

Job Name	
Model Specified	Quantity
Variations Specified	
Date	







Features & Benefits:

- Single hole, single temperature faucet w/ chrome plated
- Quarter-turn Eterna compression cartridge w/ spring check
- Lever handle w/ color coded index
- Continuous pressure vacuum breaker
- 9 ft coiled hose w/ angled high flow spray head
- 1/2" NPT female inlet
- Materials: Chrome plated body & spray head, chrome plated metal handle and polyurethane hose

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Exempt (Non-Potable)
- CSA B64.8 (VB)

Warranty: One Year (Limited)

Performance Data:

Pressure: 20 - 125 psi Temperature: 40 °F - 140 °F Flow Rate: 2.52 GPM @ 60 psi

Optional Cartridges With Checks Optional Handles

- □ 4" Wrist Action
- □ Lever (Standard)
- □ 4-Arm
- □ Quarter-Turn Cerama w/ Check Valve
- □ Quarter-Turn Eterna w/ Spring Check (Standard)









