

Epoxy Coated Retractable Hose Reels

TAG:

B-7242-C10


Enclosed Epoxy Coated Hose Reel

Architect/Engineering Specifications:

Enclosed epoxy coated hose reel, extended spray wand with swivel, 3/8" x 50' heavy-duty non-marking hose, ratcheting system, multi-fit bracket, adjustable hose bumper and 3/8" NPT female inlet.

> 8 7/16" 214mm

Job Name	
Model Specified	Quantity
Variations Specified	
Date	



Features & Benefits:

- Enclosed epoxy coated hose reel
- Extended spray wand w/ swivel
- 3/8" x 50' heavy-duty non-marking hose rated to 300 PSI
- Ratcheting system holds the length of hose until a slight tug to retract automatically
- 3/8" NPT female inlet
- Adjustable hose bumper
- Multi-fit bracket for wall, ceiling or under counter mounting
- Material: Epoxy coated steel enclosed reel, wall bracket and chrome plated brass spray valve

Product Compliance:

- NSF 61 Exempt (Non-Potable)
- EPAct 2005 Non-Compliant (PRSV)

Warranty: Two Year (Limited)

Hose: One Year (Limited)

Performance Data:

Pressure: 20 - 125 psi [1.38 - 8.62 bar]

Optional Hose Reel Multi-Fit Brackets

3/8" x 50' Epoxy Coated Hose Reel

- Temperature: 40 °F 140 °F [4.44 °C 60 °C]
- Flow Rate: 3.40 GPM [12.9 L/min] @ 60 psi [4.14 bar]

Optional Hose Reel Spray Valves

□ B-0107 Spray Valve □ B-0108

Ergonomic Medium Flow Spray Valve □ B-0108-H

□ EB-0107

Ergonomic Neddin Flow Spray Valve
Ergonomic High Flow Spray Valve
High Flow Spray Valve
Extended Spray Wand (Standard)
Stainless Steel Rear Trigger Water Gun
Stainless Steel Front Trigger Water Gun
Aluminum Rear Trigger Water Gun □ EB-2322 □ MV-2516-24 □ MV-2522-24

□ MV-3516-24

T&S BRASS AND BRONZE WORKS, INC.







□ G019430-45 EasyInstall Stainless Steel Swing Bracket

□ G016652-45 **Deck Mount Pivot Bracket**

Stainless Steel Table Leg Swing Bracket □ G018477-45