
TAG:	


Double Pantry Faucet

Architect/Engineering Specifications:

Wall mount mixing faucet with polished chrome plated brass body, 5 9/16" swivel nozzle with vacuum breaker and garden house male outlet, compression cartridges with spring checks, lever handles and 1/2" NPT female adjustable arm inlets. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9, NSF 372 and ASSE 1001. Meets ADA ANSI/ICC A117.1 requirements.

Job Name_______Quantity______Variations Specified_______Date







Features & Benefits:

- Adjustable inlet wall mount mixing faucet with polished chrome plated brass body
- 5 9/16" swing nozzle w/ vacuum breaker
- · Lock washer included for rigid applications
- · Garden hose male outlet
- Quarter-turn Eterna compression cartridges with spring checks to prevent the cross flow of water
- · Lever handles w/ color coded indexes
- 1/2" NPT female adjustable arm inlets w/ Ø2" flanges
- Adjustable centers from 2 1/4" to 8 1/4" above or below centerline
- Material: Polished chrome plated brass body & spout and chrome plated metal handles

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)
- ASSE 1001 (VB)

Warranty: One Year (Limited)

Performance Data:

Pressure: 20 - 125 psi

Temperature: 40 °F - 140 °F

• Flow Rate: 10.50 GPM @ 60 psi









Optional Cartridges With Checks

- □ Quarter-Turn Cerama w/ Check Valve
- □ Quarter-Turn Eterna w/ Spring Check (Standard)

Optional Handles

- □ 4" Wrist Action
- □ Lever (Standard)
- □ 4-Arm







T&S BRASS AND BRONZE WORKS, INC.

