
TAG:	

Swivel Pantry Faucet

Architect/Engineering Specifications:

8" wall mount mixing faucet with polished chrome plated brass body, 12" double joint swing nozzle with stream regulator outlet, compression cartridges with spring checks, lever handles and 1/2" NPT female inlets. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372. Meets ADA ANSI/ICC A117.1 requirements.



Features & Benefits:

- 8" wall mount mixing faucet with polished chrome plated brass body
- 12" double joint swing nozzle with 6" back nozzle and 6" front nozzle
- Lock washer provided for rigid application
- Stream regulator outlet, Series 1
- Quarter-turn Eterna compression cartridges w/ spring checks to prevent cross flow of water
- Lever handle w/ color coded indexes
- 1/2" NPT female eccentric inlets w/ Ø2" flanges
- Adjustable centers from 7 3/4" to 8 1/4"
- Material: Polished chrome plated brass body & tubular spouts and chrome plated metal handles

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)

Warranty: One Year (Limited)



Performance Data:

Pressure: 20 - 125 psi Temperature: 40 °F - 140 °F

Flow Rate: 19.22 GPM @ 60 psi



Optional Outlets (Series 1 / VR Series 6)

		Non-Aerated	VR Aerated	VR Non-Aerated	Optional Handles
GPM	Aerated	(Laminar)		VR Aerated	R Aerated (VR Laminar)
0.35	N/A	□ B-0199-01-N035	N/A	□ B-0199-06-N035	□ Lever (Standard)
0.5	N/A	□ B-0199-01-N05	N/A	□ B-0199-06-N05	□ 4-Arm
1.0	□ B-0199-01-F10) N/A	□ B-0199-06-F10	N/A	Optional Cartridges With Checks
1.2	□ B-0199-01-F12	2 □ B-0199-01-LF12	□ B-0199-06-F12	□ B-0199-06-LF12	
1.5	□ B-0199-01-WS	□ B-0199-29	□ B-0199-06-WS	□ B-0199-29VR	□ Quarter-Turn Cerama w/ Check Valve
2.2	□ B-0199-01	□ B-0199-21	□ B-0199-06	☐ B-0199-21-VRF	□ Quarter-Turn Eterna w/ Spring Check (Standard)







T&S BRASS AND BRONZE WORKS, INC.

