



Replacement Hoses
S-0044-H2A


TAG:

Flexible Stainless Steel Hose

Architect/Engineering Specifications:

38 5/8" flexible stainless steel hose, 7/8-20 UN female outlet and 3/4-14 UN female inlet. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372.

Job Name _____
 Model Specified _____ Quantity _____
 Variations Specified _____
 Date _____



Features & Benefits:

- 38 5/8" flexible stainless steel hose (less handle)
- Polyurethane inner tubing
- 7/8-20 UN female outlet
- 3/4-14 UN female inlet
- Hose washers included
- Material: Stainless steel end fittings and hose

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 - Section 9
- NSF 372 (Low Lead Content)

Warranty: Three Year (Limited)

Performance Data:

- Pressure: 20 - 125 psi [1.38 - 8.62 bar]
- Temperature: 40 °F - 140 °F [4.44 °C - 60 °C]
- Flow Rate: 6.25 GPM [23.66 L/min] @ 60 psi [4.14 bar]



T&S BRASS AND BRONZE WORKS, INC.



• 2 Saddleback Cove • Travelers Rest, SC 29690
 Ph 800-476-4103 • Fax 864-834-3518
 • Simi Valley, CA • Ph 800-423-0150 • www.tsbrass.com

Date: 09/15/21