

What to expect from legendary





SPECIALLY DESIGNED SPRING REINFORCEMENT

protects hose from wear.

OPTIONAL ACCESSORY TEE

provides additional water source.

OPTIONAL: MULTIPLE LENGTH WALL BRACKETS AVAILABLE

designed with ability to be cut in the field to desired length.

50% THICKER NOZZLE AND RISER THICKNESS VS. COMPETITORS

for ultimate durability.

MODELS WITH AND WITHOUT ADD-ON FAUCETS AVAILABLE.

1/4-TURN CARTRIDGES WITH CROSS-FLOW PREVENTION

¼ turn design with two cartridge options to best suit your water conditions: Eterna compression (perfect for areas with harsh water conditions), or Cerama ceramic cartridges (rated to 180 °F and featuring lifetime warranty).

STAINLESS STEEL HOSES WITH DOUBLE INTERLOCKED BRAIDS AND REINFORCED POLYURETHANE INNER TUBING

for long life. Pressure rated to 125 psi.

OPTIONAL: 360-DEGREE ROTATION OF SPRAY VALVE WITH ADD-ON SWIVEL

reduces employee strain and extends hose life.

INSULATED HANDLE

provides a cool grip.

RANGE OF SPRAY VALVE OPTIONS AVAILABLE

from 0.65 GPM to 1.15 GPM for top performance and water conservation. Meet DOE regulations. Tested to over 1.5 million cycles.

PREASSEMBLED PARTS

reduce installation time.

INTERLOCKING SPLINES PREVENT WALKING

by keeping the handles in the original set position.

ECCENTRIC FLANGES

allow for alignment and easy installation in the field.











EASYINSTALL DESIGN

reduces installation time and hassle.



CUSTOM UNITS

from 5 key styles, optional accessories to interchangeable parts.



for easy installation for wall mount PRUs.