

## **Electronic Faucets**

# Electronic Sensor Faucet


TAG:


## 5EF-1D-DS

### **Architect/Engineering Specifications:**

Single hole deck mount electronic sensor faucet with polished chrome plated brass body, 2.2 GPM vandal resistant aerator, AC/DC control module, temperature control mixing valve with integral check valves and 18" flexible stainless steel supply hoses with 3/8" compression connections. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9, NSF 372 and UL 1951. Meets ADA ANSI/ICC A117.1 requirements

Job Name	
Model Specified	Quantity
Variations Specified	
Date	







#### Features & Benefits:

- Single hole deck mount faucet w/ polished chrome plated brass body
- 2.2 GPM vandal resistant aerator, Series 9 (B-0199-09)
- Water resistant control module
- Plug in AC transformer or (4) AA battery (DC) power options
- Temperature control mixing valve w/ integral check valves
- 18" flexible stainless steel supply hoses w/ 3/8" compression connections
- Low battery LED indicator light
- Material: Polished chrome plated brass body & spout

#### **Product Compliance:**



- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)
- UL 1951



Warranty: One Year (Limited)



## Performance Data:

- Pressure: 20 125 psi [1.38 8.62 bar]
- Temperature: 40°F 140°F [4.44°C 60°C]
- Flow Rate: 2.2 GPM [8.3 L/min] @ 60 psi [4.14 bar]
- Water Consumption: @10 sec = .37 gal [1.40 L]

@15 sec =	.55 ga	1 [2.08

#### Non-Aerated VR Non-Aerated **GPM Aerated VR** Aerated **Optional Deck Plates** (Laminar) (VR Laminar) 0.35 N/A □ B-0199-04-N035 N/A □ B-0199-09-N035 □ 4" Chrome Plated Brass Deck Plate □ B-0199-04-N05 □ 8" Chrome Plated Brass Deck Plate 0.5 N/A N/A □ B-0199-09-N05 1.0 N/A N/A N/A □ B-0199-09-LF10 1.5 □ B-0199-04-WS N/A □ B-0199-09-WS □ B-0199-09-LF15 2.2 □ B-0199-04 □ B-0199-25 Standard □ B-0199-27







equip Foodservice Accessories

Optional Outlets (Series 4 / VR Series 9)

