T	٠,	C	•	
ı	\neg	J	•	


Wash and Rinse Faucets


Architect/Engineering Specifications:

Adjustable wall mount mixing faucet with polished chrome plated brass body, vacuum breaker with garden hose male adapter, compression cartridges with spring checks, lever handles and 1/2" NPT female adjustable arm inlets. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9, NSF 372 and CSA B64.8. Meets ADA ANSI/ICC A117.1 requirements.

Job Name			
Model Specified	Quantity		
Variations Specified			
Date			







Features & Benefits:

- Adjustable inlet wall mount mixing faucet with polished chrome plated brass body
- EasyInstall vacuum breaker for quick installation
- Male garden hose adapter
- Quarter-turn Eterna compression cartridges with spring checks to prevent crossflow of water
- · Lever handles w/ color coded indexes
- 1/2" NPT female adjustable arm inlets w/ ∅ 2" flanges
- Adjustable centers from 2 1/4" to 8 1/4" above or below centerline
- Material: Polished chrome plated brass body & chrome plated metal handles

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)
- CSA B64.8 (VB)

Warranty: One Year (Limited)

Performance Data:

Pressure: 20 - 125 psiTemperature: 40 °F - 140 °F

• Flow Rate: 7.27 GPM @ 60 psi



Optional Cartridges With Checks

- ☐ Quarter-Turn Cerama w/ Check Valve
- □ Quarter-Turn Eterna w/ Spring Check (Standard)

Optional Handles

- □ 4" Wrist Action
- □ Lever (Standard)
- □ 4-Arm







T&S BRASS AND BRONZE WORKS, INC.

