


| TAG: | |
|------|--|
| | |

Pot Filler Faucet

Architect/Engineering Specifications:

Single hole deck mount mixing faucet with polished chrome plated brass body, 90 ° swivel arm adapter, 60" flexible stainless steel hose, heat resistant handle, self closing pot filler valve with hook nozzle, ceramic cartridge with check valve, lever handle, 1/2" NPSM male inlet and wall hook. Certified to ASME A112.18.1 / CSA B125.1, NSF 61-Section 9 and NSF 372.







Features & Benefits:

- Single hole deck mount mixing faucet w/ polished chrome plated brass body
- · Lock washer provided for rigid application
- 90° swivel arm adapter
- 60" flexible stainless steel hose w/ heat resistant gray handle and hold down ring
- Self closing pot filler valve with hook nozzle
- · Quarter-turn Cerama cartridge w/ check valve
- Lever handles w/ color coded index
- 1/2" NPSM male inlet
- · Wall hook holds spray valve when not in use
- Material: Polished chrome plated brass body and spray valve body, stainless steel hose and chrome plated metal handle

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- 2019 DOE PRSV Non-Compliant

Warranty: One Year (Limited)


· Cerama Cartridge: Lifetime (Limited)

Performance Data:

Pressure: 20 - 125 psi
Temperature: 40 °F - 140 °F
Flow Rate: 2.38 GPM @ 60 psi

SP ®





☐ 4" Wrist Action

□ Lever (Standard)

□ 4-Arm

Optional Cartridges With Checks

□ Quarter-Turn Cerama w/ Check Valve (Standard)

□ Quarter-Turn Eterna w/ Spring Check







T&S BRASS AND BRONZE WORKS, INC.

